

## ESTECH All-In-One Domestic Heat PumpWater Heater Side Air Outlet Type



**ESTECH ENERGY LLC** 



### All In One Domestic Heat Pump Water Heater



Integral Design compact structure and space saving.



Energy-Efficient saving electricity 75%.



Defrost Automatically safe use in winter.

Internet of Things remote control and leading intelligent service.



75°C hot water high temperature hot water meets more customer demands.

Enamel Tank / Stainless Steel Tank resistant to rust and no furring.





#### Specifications

**Top Air Outlet Type** 



| Model                            | IU | WHP-200       | WHP-250      | WHP-300      |
|----------------------------------|----|---------------|--------------|--------------|
| Hot Water Capacity               | kw | 2.5           | 2.5          | 2.5          |
| Power Input                      | kw | 0.6           | 0.6          | 0.6          |
| COP                              |    | 4.16          | 4.16         | 4.16         |
| Max Power Input                  | kw | 3             | 3            | 3            |
| Rated Current                    | А  | 2.7           | 2.7          | 2.7          |
| MaxCurrent                       | А  | 15            | 15           | 15           |
| Power Supply                     |    | 220V/1Ph/50Hz |              |              |
| Electric Heater                  | W  | 2000          | 2000         | 2000         |
| Refrigerant                      |    | R134a         | R134a        | R134a        |
| NetDimension                     | mm | 620/1638      | 620/1868     | 620/2038     |
| Package Dimension                | mm | 700/700/1830  | 700/700/2060 | 700/700/2230 |
| Net Weight                       | kg | 88            | 95           | 102          |
| Gross Weight                     | kg | 106           | 113          | 120          |
| Noise                            | dB | 48            | 48           | 48           |
| Water Tank Volume                | L  | 200           | 250          | 300          |
| Temperature Range                | °C | - 7~43        | - 7~43       | - 7~43       |
| Loading Quantity(20ft container) |    | 24            | 24           | 24           |
| Loading Quantity(40ft container) |    | 51            | 51           | 51           |

Testing condition: ambient temperature 20  $^\circ\text{C}/15\,^\circ\text{C}$  , water circulation from 55  $^\circ\text{C}$  .

The above data is for reference only.For more specific data, refer to the nameplate on the unit.

High quality-We believe that quality is the best business plan

R&D team-Professional R&D team for new and high-efficiency heat pumps

Reasonable prices-Competitive prices which help you to occupy your market

Heat pumps

**ESTECH** 

ENERGY

Best components-World class components suppliers for your heat pumps

Fast delivery-

We always keep the promise to you, you always keep the promise to your customers

Long warranty-TWO years for heat pumps, THREE years warranty for Compressor and Condenser

# ESTECH ENERGY

#### **ESTECH ENERGY LLC**

Estech Energy LLC. Address: 4228, Hamphire Lane, El Paso, TX 79902 E-mail: mail@estechenergy.com Web: www.estechenergy.com